



FIELD TILES		
SIZE	SIZE SPECIFICATIONS	THICKNESS*
UNDULATED TILE		
2.5"x5.1"	2.520"x5.118" (64mm x 130mm)	0.295" (7.5mm)
2.5"x10.3"	2.520"x10.315" (64mm x 262mm)	0.303" (7.7mm)
5.1"x5.1"	5.118"x5.118" (130mm x 130mm)	0.303" (7.7mm)
DECORATIVE ACCESORIES & FINISHING TOUCHES		
Liner (One Overglazed Edge) 0.6"x10.3"	0.630"x10.315" (16mm x 262mm)	0.354" (9mm)
Quarter Round 1"x10.3"	1.024"x10.315" (26mm x 262mm)	0.394" (10mm)
Molding 2"x10.3"	2.008"x10.315" (51mm x 262mm)	0.591" (15mm)
Base Board (Glazed Top Edge) 4"x10.3"	3.976"x10.315" (101mm x 262mm)	0.551" (14mm)
APPLICATIONS		
	SUITABLE RESIDENTIAL	SUITABLE COMMERCIAL
Bathroom Walls	YES	YES
Shower Walls	YES	YES
Kitchen Walls	YES	YES
Countertops	YES	NO
Fireplace Surrounds	YES	YES
Outdoor Cooking / Bar Spaces	YES	YES
Pool Waterlines / Water Fountains	NO	NO
Floors	NO	NO
PERFORMANCE CHARACTERISTICS		
	TEST METHOD ATSM / ISO	RESULT
Water Absorption	C-373 / 10545-3	Pass
Breaking Strength	C-648 / 10545-4	Pass
Chemical Resistance	C-651 / 10545-14	Resistant
Facial Dimensions	C-499 / 10545-2	Pass
Range of Thickness	C-499 / 10545-2	Pass
Warpage	C-485 / 10545-2	Pass

*Thickness is understood as the highest point of the tile.

INSTALLATION	
GROUT JOINT RECOMMENDATION	SHADE VARIATION
1/8"	V3 - Moderate Variation

CLEANING RECOMMENDATIONS
Routine with a non-abrasive/non-acidic, mild and PH neutral cleaner

CHARACTERISTICS	
Glaze	Solid with subtle movement and high color variation
Surface Sheen	Glossy and Matte
Texture	Slightly Undulated

Due to the nature of our tile, a certain amount of variation in color, shading, surface and texture are to be expected.

This collection is characterized by its shade variation. Some colors in the series have more variation than others. Expect shade variation between the individual field tiles and between field and trim within each color. Due to the shape of the pieces and the nature of production, this is especially true for variation between field and trims. Trim pieces like quarter rounds, finishing edges and other moldings may have more glaze pooling and different pooling effects than other pieces. Expect variation within each run, and from production to production. IT IS IMPORTANT TO BLEND TILE WITHIN EACH CARTON AND FROM MULTIPLE CARTONS DURING INSTALLATION. This is best achieved by laying out the material prior to installation.