



FIELD TILES		
SIZE	SIZE SPECIFICATIONS	THICKNESS*
MESH MOUNTED		
Penny Rounds 3/4" 12.38" x 11.50"	12.362"x11.496" (314mm x 292mm)	0.157" (4mm)
Hexagons 1" 11.97" x 11.69"	11.967"x11.693" (303.97mm x 297mm)	0.236" (6mm)
APPLICATIONS		
	SUITABLE RESIDENTIAL	SUITABLE COMMERCIAL
Bathroom Walls	YES	YES
Shower Walls	YES	YES
Kitchen Walls	YES	YES
Countertops	NO	NO
Fireplace Surrounds	YES	YES
Outdoor Cooking / Bar Spaces	YES	YES
Pool Waterlines / Water Fountains**	YES	YES
Floors***	YES	NO
PERFORMANCE CHARACTERISTICS		
	TEST METHOD ATSM / ISO	RESULT
Water Absorption	C-373 / 10545-3	0.00%
Breaking Strength	C-648 / 10545-4	N/A
Chemical Resistance	C-651 / 10545-14	Resistant
Facial Dimensions	C-499 / 10545-2	Avg. 18.741mm
Range of Thickness	C-499 / 10545-2	Avg. 4.924mm
Warpage	C-485 / 10545-2	0

INSTALLATION	
GROUT JOINT RECOMMENDATION	SHADE VARIATION
5/64"	V2 - Slight Variation

CLEANING RECOMMENDATIONS
Routine with a non-abrasive/non-acidic, mild and PH neutral cleaner

CHARACTERISTICS	
Glaze	Solid with subtle movement
Surface Sheen	Glossy & Matte
Texture	Slightly Undulated

*Thickness is understood as the highest point of the tile.

**Not recommended for freeze-thaw environments.

*** Only Matte Colors (White and Black) and for residential use.

Due to the nature of our tile, a certain amount of variation in color, shading, surface and texture are to be expected.