



ADEX
since 1897



DIAMONDS COLLECTION

DIAMONDS Dimensional Field

Glossy Finish


AVAILABLE COLORS

White **ADNZ** Bone **ADNB**

Find out the product code simply by putting together the color and the item

Example: **ADNZ** **684**

FLAT




684 8"x4" Flat

PILLOW




884 8"x4" Pillow



881 4"x4" Half Pillow

PILLOW SILVER



ADMS 884 8"x4" Pillow Silver

White and Bone Diamonds are color coordinated with the Neri collection.

ACCENT DOTS 3/4"x3/4"

Ceramic Flat



ADNZ 6840
Accent Dot White



ADNB 6840
Accent Dot Bone



ADNSS 6840
Accent Dot Sierra Sand



ADNSM 6840
Accent Dot Silvert Mist



ADNS 6840
Accent Dot Silver



ADNG 6840
Accent Dot Gold



ADNK 6840
Accent Dot Black

White, Bone, Sierra Sand, Silver Mist and Black Flat Dots are color coordinated with the Neri collection.

ACCENT DOTS 3/4"x3/4"

Ceramic Sphere



ADNZ 6842
Accent Dot White



ADNB 6842
Accent Dot Bone



ADNSS 6842
Accent Dot Sierra Sand



ADNSM 6842
Accent Dot Silvert Mist



ADNS 6842
Accent Dot Silver



ADNG 6842
Accent Dot Gold



ADNK 6842
Accent Dot Black



ADNR 6842
Accent Dot Red

White, Bone, Sierra Sand, Silver Mist and Black Sphere Dots are color coordinated with the Neri collection.



ADNZ White

DIAMONDS



FIELD TILES		
SIZE	SIZE SPECIFICATIONS	THICKNESS*
FLAT TILE		
8"x4"	7.834"x3.937" (199mm x 100mm)	0.354" (9mm)
PILLOW TILE		
8"x4" Pillow	7.834"x3.937" (199mm x 100mm)	0.567" (14.4mm)
FLAT DOT		
3/4"x3/4"	0.827"x0.827" (21mm x 21mm)	0.354" (9mm)
SPHERE DOT		
3/4"x3/4"	0.787"x0.787" (20mm x 20mm)	0.622" (15.8mm)
APPLICATIONS		
	SUITABLE RESIDENTIAL	SUITABLE COMMERCIAL
Bathroom Walls	YES	YES
Shower Walls	YES	YES
Kitchen Walls	YES	YES
Countertops	NO	NO
Fireplace Surrounds**	YES	YES
Outdoor Cooking / Bar Spaces	YES	YES
Pool Waterlines / Water Fountains	NO	NO
Floors	NO	NO
PERFORMANCE CHARACTERISTICS		
	TEST METHOD ATSM / ISO	RESULT
Water Absorption	C-373 / 10545-3	Pass
Breaking Strength	C-648 / 10545-4	Pass
Chemical Resistance	C-651 / 10545-14	Resistant
Facial Dimensions	C-499 / 10545-2	Pass
Range of Thickness	C-499 / 10545-2	Pass
Warpage	C-485 / 10545-2	Pass

INSTALLATION	
GROUT JOINT RECOMMENDATION	SHADE VARIATION
1/8"	V1 - Uniform Appearance

CLEANING RECOMMENDATIONS
Routine with a non-abrasive/non-acidic, mild and PH neutral cleaner

CHARACTERISTICS	
Glaze	Solid
Surface Sheen	Glossy
Texture	Smooth

*Thickness is understood as the highest point of the tile.

**This usage excludes the Silver Diamonds.

Due to the nature of our tile, a certain amount of variation in color, shading, surface and texture are to be expected.



CONTACT US

Corporate Headquarters

South East Distribution Center

9450 N.W.12th St.
Miami, FL 33172
Office: 305-513-4633
Fax: 305-513-4634
customerservice@adexusa.com

West Coast Distribution Center

2344 E. Walnut Ave.
Fullerton, CA 92831
Office: 714-773-0197
Fax: 714-773-9352
customerservicewest@adexusa.com

North East Distribution Center

1000 Wall St. W.
Lyndhurst, NJ 07071
Office: 201-355-8772
Fax: 201-636-2802
customerservicene@adexusa.com



Our company has an environmental management system in place according to the Norm ISO 14001 certified by European Quality Assurance (EQA)